

ESPECIFICACIONES DE PRODUCTO

TECHNICAL DATA SHEET

Código: ST
Rev: 0

CALIDAD Grade	SECURITAS	NEUTRO	95
------------------	-----------	--------	----

CARACTERÍSTICA Property	UNIDAD Unit	MEDIA Average	TOLERANCIA Range		NORMA Estándar
			Min	Max	
GRAMAJE Weight	gr/m2	95	91,2	98,8	UNE-EN ISO 536
ESPESOR Thickness	μ	123,5	114,0	133,4	UNE-EN ISO 534
POROSIDAD Porosity	ml/min	600	400	800	UNE-EN ISO 5636-3
BLANCURA (457nm) Brightness (457nm)	% ISO	—	> 80	—	ISO 2470
LISURA CT Smoothness (inside)	ml/min	200	150	250	UNE-57080-2 ISO 8791-2
LISURA CF Smoothness (outside)	ml/min	200	150	250	UNE-57080-2 ISO 8791-3
MANO Bulk	cm3/gr	1,3	1,25	1,35	UNE-EN ISO 534
HUMEDAD Moisture	%	6,5	6	7	UNE-ISO 287
RESISTENCIA L Tensile strength	m	6500	5000	8000	UNE-EN ISO 1924-2
RESISTENCIA T Tensile strength	m	4500	3000	6000	UNE-EN ISO 1924-3
ENCOLADO COBB 60" TELA Sizing Cobb 60" (inside)	gr.H ₂ O	25	20	30	UNE-EN ISO 535
ENCOLADO COBB 60" FIELTRO Sizing Cobb 60" (outside)	gr.H ₂ O	25	20	30	UNE-EN ISO 536

Aprobado por:
Fecha: