

PP Bright Silver TC / A292 / GW62



Facestock

PP Bright Silver TC

Description Glossy, silver metallized polypropylene film, laminated with transparent polypropylene film. Top coated for printing.

Applications Suitable for labels for generic use, in particular for household products. The construction of the film prevents the deterioration of the metallization on due to an external agent.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	42	
Thickness	ISO 534	µm	60	54 - 66

Adhesive

A292

Description Clear adhesive that exhibits excellent UV and weather resistance, together with good adhesion performance, even on non-polar substrates.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/inch	11	≥ 9
Tack (Quick Stick stainless steel)	FTM 9	inch	13	≥11
Shear (1kg, in ² /glass)	FTM 8	hours	7	≥5
Minimum labelling temperature		°C	+5°C	
Minimum service temperature		°C	-30°C	
Maximum service temperature.		°C	+120°C	

Liner

Glassine White 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	57	55.9 - 58.5
Thickness	ISO 534	µm	49	47 - 51

* Values are subject to change without notice. Last updated 01/01/2025.

* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001** and **EMAS** and has successfully completed audits for **ISO 50001**, **ISO 9001** and **ISO 45001** certification. Adestor paper products are available with **PEFC** and **FSC®** C011032 chain of custody certificates upon request.