

# PP Gloss White S TC / A292F / GW



Facestock

## PP Gloss White S TC

**Description** White gloss top-coated BOPP. Good temperature and chemicals resistance. Good moisture barrier properties

**Color** White

**Finish** Gloss

**Applications** High quality labelling of cosmetics and toiletries where durability and resistance to moisture and chemicals are required. Also recommended for the labelling of fruits and vegetables.

**Printing techniques** Suitable for printing on flexo solvent-base, UV flexo, flexo water-based, hot stamping, conventional offset, offset UV, screen printing, letterpress (conventional and UV).

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m2	55	50.5 - 58.1
Thickness	ISO 534	µm	57	± 10%
Dimensional stability 100°C 10min MD	ASTM D 1204	%	-3	± 3

Adhesive

## A292F

**Description** A clear adhesive featuring excellent UV resistance and weatherability. Good adhesion performance, even on apolar substrates. Suitable for contact with dry, moist and fatty foods with a reduction factor of 3.

**Shelf life** From the date of manufacture 2 years in 20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N	10	≥ 8
Tack (Quick Stick stainless steel)	FTM 9	N	9,2	≥ 7,8
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	hours	50	≥ 25
Minimum labelling temperature		°C	+5°C	
Minimum service temperature		°C	-30°C	
Maximum service temperature.		°C	+120°C	

Liner

## Glassine White 62

**Description** Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

**Color** White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m2	57	55.9 - 58.5
Thickness	ISO 534	µm	49	47 - 51

\* Values are subject to change without notice. Last updated 01/01/2025.

\* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001** and **EMAS** and has successfully completed audits for **ISO 50001**, **ISO 9001** and **ISO 45001** certification. Adestor paper products are available with **PEFC** and **FSC®** C011032 chain of custody certificates upon request.