

ESPECIFICACIONES DE PRODUCTO

TECHNICAL DATA SHEET

Código: CPC
 Rev:

CALIDAD Grade	ROTO FORM COLOR PLUS	160
-------------------------	-----------------------------	------------

CARACTERISTICA Property	UNIDAD Unit	MEDIA Average	TOLERANCIA Range		NORMA Estándar
			Min	Max	
GRAMAJE Weight	gr/m2	160	153,6	166,4	UNE-EN ISO 536
ESPESOR Thickness	μ	208	184,3	228,0	UNE-EN ISO 534
POROSIDAD Porosity	ml/min	1000	600	1500	UNE-EN ISO 5636-3
COLOR Colour	CMC (1:1)	0	0	< 1	ISO 105-J03
LISURA CT Smoothness (inside)	ml/min	220	100	700	UNE-57080-2 ISO 8791-2
LISURA CF Smoothness (outside)	ml/min	280	100	800	UNE-57080-2 ISO 8791-3
MANO Bulk	cm3/gr	1,3	1,2	1,37	UNE-EN ISO 534
HUMEDAD Moisture	%	4,5	3,5	5,5	UNE-ISO 287
RESISTENCIA L Tensile strenght	m	5000	4000	7000	UNE-EN ISO 1924-2
RESISTENCIA T Tensile strenght	m	3000	2500	5000	UNE-EN ISO 1924-3
ENCOLADO COBB 60" TELA Sizing Cobb 60" (inside)	gr.H ₂ O	—	25	35	UNE-EN ISO 535
ENCOLADO COBB 60" FIELTRO Sizing Cobb 60" (outside)	gr.H ₂ O	—	25	35	UNE-EN ISO 536

Aprobado por:
 Fecha: