

ESPECIFICACIONES DE PRODUCTO

TECHNICAL DATA SHEET

Código: CPP
Rev:

CALIDAD Grade	ROTO FORM COLOR PLUS	60
------------------	----------------------	----

CARACTERISTICA Property	UNIDAD Unit	MEDIA Average	TOLERANCIA Range		NORMA Estándar
			Min	Max	
GRAMAJE Weight	gr/m2	60	57,6	62,4	UNE-EN ISO 536
ESPEJOR Thickness	μ	78	72,0	84,2	UNE-EN ISO 534
POROSIDAD Porosity	ml/min	1000	600	1500	UNE-EN ISO 5636-3
COLOR Colour	CMC (1:1)	0	0	< 1	ISO 105-J03
LISURA CT Smoothness (inside)	ml/min	180	100	500	UNE-57080-2 ISO 8791-2
LISURA CF Smoothness (outside)	ml/min	190	100	550	UNE-57080-2 ISO 8791-3
MANO Bulk	cm3/gr	1,3	1,25	1,35	UNE-EN ISO 534
HUMEDAD Moisture	%	4,7	4	6	UNE-ISO 287
RESISTENCIA L Tensile strenght	m	6000	5000	8000	UNE-EN ISO 1924-2
RESISTENCIA T Tensile strenght	m	3500	3000	5000	UNE-EN ISO 1924-3
ENCOLADO COBB 60" TELA Sizing Cobb 60" (inside)	gr.H ₂ O	—	22	35	UNE-EN ISO 535
ENCOLADO COBB 60" FIELTRO Sizing Cobb 60" (outside)	gr.H ₂ O	—	22	35	UNE-EN ISO 536

Aprobado por:
Fecha: