

ESPECIFICACIONES DE PRODUCTO

TECHNICAL DATA SHEET

Código: CXL
Rev:

CALIDAD Grade	EDICIÓN 135
-------------------------	------------------------------

CARACTERISTICA Property	UNIDAD Unit	MEDIA Average	TOLERANCIA Range		NORMA Estándar
			Min	Max	
GRAMAJE Weight	gr/m2	135	129,6	140,4	UNE-EN ISO 536
ESPESOR Thickness	μ	168,75	155,5	182,5	UNE-EN ISO 534
POROSIDAD Porosity	ml/min	800	600	1000	UNE-EN ISO 5636-3
BLANCURA (457nm) Brightness (457nm)	% ISO	106	104	108	ISO 2470
BLANCURA CIE Whiteness CIE	% ISO	144	142	146	ISO 11475
COLOR Colour	CMC (1:1)	0	0	< 0,7	ISO 105-J03
LISURA CT Smoothness (inside)	ml/min	200	100	280	UNE-57080-2 ISO 8791-2
LISURA CF Smoothness (outside)	ml/min	220	120	300	UNE-57080-2 ISO 8791-3
MANO Bulk	cm3/gr	1,25	1,2	1,3	UNE-EN ISO 534
HUMEDAD Moisture	%	6,0	5,5	6,5	UNE-ISO 287
RESISTENCIA L Tensile strength	m	7200	5500	9500	UNE-EN ISO 1924-2
RESISTENCIA T Tensile strength	m	4000	3000	5500	UNE-EN ISO 1924-3
ENCOLADO COBB 60" TELA Sizing Cobb 60" (inside)	gr.H ₂ O	30	25	35	UNE-EN ISO 535
ENCOLADO COBB 60" FIELTRO Sizing Cobb 60" (outside)	gr.H ₂ O	28	25	35	UNE-EN ISO 536

Aprobado por:
Fecha: